



L						
5.	28 AWG., 36 Conductors + Drain Wire, Single Shielded with	XX	FT.			
	AL-FOIL, Beige Outer PVC jacket					
4.	Beige Molded PVC Hood, Fully Shielded w/AL-FOIL	1	PCS.			
3.	Centronics 36 Pin Female W/Gold Plating Contacts	1	PCS.			
2.	Beige Molded PVC Hood, Fully Shielded w/AL-FOIL	1	PCS.			
1.	Centronics 36 Pin Male W/Gold Plating Contacts	1	PCS.			
ITEM No.	MATER]AL / SPECIFICATION	REDI	UNIT			
CABLE ASSEMBLY PARTS LIST						

	UNLESS OTHERWISE SPECIFIE
	1. DINENSION ARE IN INCHS
	2. TOLERANCES:
	DECIMALES X.XX ±0.25
_	3. DO NOT SCALE DRAVING
	4. REMOVE ALL BURRS AND
_	BREAK SHARP EDGES.
	COCCOTETACK DECUMENT

PROPRIETARY DOCUMENT
HES DRAVING AKO/OR INFORMATION OR
LIBLECT HATTER CONTAINED HEREIN,
HALL NOT BE USED, COPIED OR
ISSENJNATED IN ANY HANNER, OR FOR
NY PURPOSE, OTHER THAN AS
XPRESSLY STATED BY

CUSTONER		
R.F.Q. NO.		
IRAWN	DATE	Ŀ
Howle Tseng	05/18/94	יו
CHECKED		ı
		ı
CUSTOMER APPROVAL		9

PCCABLES.COM

Centronics Parallel Extension Cable CN36-M CN36-F

SIZE			. 000	33			REV.
SCALE	NDE	RELEASE DATE:	05/18/94	SHEETI	1	Œ	1